SPECIFICATIONS

41650 SS Drain 12" Square Top, 10" Deep Specification

Josam series 41650 fabricated stainless steel (type 304, 14 GA), 12" square top, 10" deep, with no-hub bottom outlet, anchor tabs and perforated SS grate (standard).





STANDARD GRATE







-CWD	Can wash drain	-F	Flange, anchor		Model
-NB	Nickel bronze rim & grate (*add 0.5")	-CF	Clamp and flange		41653
-FB	Filter basket	-BW	Butt-weld outlet (spec. 10, 40, 80)		41654
-SB	Sediment bucket	-NG	No grate		41656
-VP	Secured grate	-HG	Perf. Half grate		
-DB	Dome bottom strainer	-3Q	Perf. 3/4 grate		
-SO	Side outlet	-MG	Mesh, anti-slip grate		
-50	1/2" primer tap	-LG	Ladder grate		
-WH	Weepholes (1 per side, $ otin 1/8 $ ")	-SG	Perimeter slot grate		
-т	Threaded outlet	-316	Type 316L material		
-PFO	Push-Fit size outlet	-DB	Dome bottom strainer		
-WF	Wide flange				

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



A WATTS Brand

T: (800) 365-6726 • Josam.com

Pipe size 3" 4"