SPECIFICATIONS

STANDARD GRATE FREE AREA = 42.4 IN^2 MEETS ADA AND HEEL-PROOF REQMT.

42630 SS Drain 12" Round Top, 6" Deep Specification

Josam series 42630 fabricated stainless steel (type 304), 12" round top, 6" deep, with no-hub bottom outlet, anchor tabs and perforated SS grate (standard).







OPTIONS:

 -		-			 _		
-FB	Filter basket		-WH	Weepholes 1/8" (3X)		Model	Pipe size
-SB	Sediment bucket		-NG	No grate		42633	3"
-VP	Secured grate		-HG	Perf. Half grate		42634	4"
-BW	Butt-Weld outlet (spec. 10,40,80)		-3Q	Perf. 3/4 grate		42636	6"
-50	1/2" Primer tap		-MG	Mesh, anti-slip grate			
-T	Threaded outlet		-LG	Ladder grate			
-F	Flange only		-SG	Perimeter slot grate			
-CF	Clamp and flange]	-316	Type 316L material			
-PFO	Push-Fit outlet		-DB	Dome bottom strainer			

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



A WATTS Brand

T: (800) 365-6726 • Josam.com