SPECIFICATIONS

43350 SS Drain Adjustable, 6" Sq. Top Specification

Josam series 43350 fabricated stainless steel (type 304), adjustable 6" square top, with no-hub bottom outlet, leveling feet, membrane clamp and perforated SS grate.

В B Ø10 1/2 [266] 5 7/8 SQ FILTER BASKET (-FB OPTION) [150] 2 - 5 1/8 GASKET [50 - 130] REMOVE O-RING FOR SECONDARY 5 11/16 DRAINAGE [145] PRIMER TAP 2 3/8 (-50 OPTION) [60] PIPE SIZE Ø5 3/8 [137]

5 11/16SQ. [145]



OPTIONS:

-FB	Filter basket	
-SB	Sediment bucket	
-VP	Secured gratte	
-50	1/2" primer tap	
-BW	Butt-weld outlet (spec. 10, 40, 80)	
-PFO	Push-Fit outlet	
-DB	Dome bottom strainer	

-Т	Threaded outlet
-NG	No grate
-HG	Perf. half grate
-3Q	Perf. 3/4 grate
-LG	Ladder grate
-316	Type 316L material

Model	Pipe size
43352	2"
43353	3"

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



A WATTS Brand

T: (800) 365-6726 • Josam.com

STANDARD GRATE FREE AREA = 11.5 IN² MEETS ADA AND HEEL-PROOF REQMT.